

# Series FA Fire Apparatus Gauge – 4.5” Duplex

## Overview

- Original Span Design Fire Apparatus Gauge
- Master Gauges for Intake and Discharge
- Made in the USA

## Benefits

- Full 4.5” Dial for Easy Readability
- “Kem-X” Freeze and Clog Proof
- Easy Mounting System

## Standard Features

- Case Material: Zytel Nylon
- Bezel Material: Polished Stainless Steel
- Socket: 1/4” NPT Male Brass Lower Back Connection
- Kem-X: Installed In 1/4” Brass Socket
- Bourdon Tube: Phosphor Bronze
- Lens: Acrylic
- Fill Fluid: Non Yellowing Low Temperature Interlube – Rated -40 to +150 F Service
- Dial: Aluminum, Two-Sided Baked Enamel Finish
- Accuracy: 2% Full Scale
- Ranges: 0-400, PSI, PSI/KPA, PSI/BAR or KPA Only
- Pointer: Black Aluminum  
Red Aluminum
- Mounting: One Piece Mounting Bracket with Adhesive Gasket for Waterproof Seal
- Gaskets: EPDM



## Available Options

- Led Lighted Glycerin Filled; White, Red, Blue, Green
- Custom Dial Faces Available Upon Request
- Metric and Other Ranges Available Upon Request
- “Dot” Swivel Elbow Installed – Dot Approved

---

### Thuemling Instrument Group

1225 Pearl Street, Waukesha, WI 53186 • Phone: 262-547-1789 • Fax: 262-547-6493  
Web: [www.thuemling.com](http://www.thuemling.com) • Email: [thuemling@earthlink.net](mailto:thuemling@earthlink.net)

© 2016 Copyright Thuemling Instrument Group



## Series FA Fire Apparatus Gauge – 4.5" Duplex

### Ordering Guide

#### DESCRIPTION:

FA-DPX = Fire Apparatus Style Liquid Fillable, Panel Mount, Bright Chrome Bezel And Kem-X Freeze-Proof Feature.

#### PREFIX:

DPX410

#### RANGE: (Please Specify)

0 - 400 PSI	0 - 400 PSI/KPA
0 - 2800 KPA	0 - 400 PSI/BAR

#### FILL: (Specify by Letter)

G = Interlube Liquid filled      D = Dry - No Fill

#### OPTIONS: (Please Specify)

LED = LED Back Lighted Gauge  
 DOT = Swivel Elbow Installed

#### EXAMPLE:

DPX410 - 400 PSI - G  
 Panel Cut-Out 4.85"

